Description:

TechnoFix® SRA are special grade formulated quartz aggregates used with various resin products to produce heavy duty resinous industrial floors filled coatings and slipresistant profiles, mortars aiming at the increase of hardness, traction or other characteristics, such as improving of slip-resistant ,walkability, etc.

TechnoFix® SRA are designed to increase the impact and slip resistance of resinous industrial coatings and flooring systems. TechnoFix® SRA Also used to increase the bond between concrete substrates and multi-layer systems and to provide a mechanical key for overlay systems.

Application Includes:

TechnoFix® SRA when used as per the relevant method statements for Techno Builders Solutions® can be used in locations such as:

- Car Park Decks
- Factories & Warehouses
- Aircraft Hangars
- Loading Bays
- Automobile Garages & Engineering Workshops
- **Power Stations**
- Abattoirs

Features:

- Wear resistant
- Slip resistant
- Non-oxidising
- Economical
- High impact.
- Improves bond
- Zero VOC quartz sand contain zero volatile organic content and are safe for use, both outdoors and in confined indoor spaces.
- Wide range of application, due to gradation aggregates.

Packaging

TechnoFix® SRA are available in 30kg HDPE Bags.

Identification & Grading

TechnoFix® SRA - 1-0-0.3mm, TechnoFix® SRA -3-0.3-0.9mm, TechnoFix® SRA -5-1-2mm

Shelf Life

The shelf life is 36 months if stored as per the recommendations. In a covered and secured storage space.

Coverage

As per the relevant Techno Builders Solutions Product Method Statements.

Health and Safety instructions

TechnoFix® SRA aggregates are inert and harmless, however, as with other products containing Portland cement and resins, TechnoFix® SRA mixes may cause irritation. In case of contact with eyes, immediately flush with plenty of water for at least 15 minutes. Call a physician. In case of contact with skin, wash skin thoroughly. Read the product label and Material Safety Data Sheet (MSDS) before use. Users should acquaint themselves with all risk and safety phrases.

Storage

Store out of direct sunlight, clear of the ground on pallets protected from rainfall.

Avoid excessive compaction. Product only for professional use.

DISCLAIMER: The product information & application details given by the company & its agents has been provided in good faith & meant to serve only as a general guideline during usage. Users are advised to carry out tests & take trials to ensure on the suitability of products meeting their requirement prior to full scale usage of our products. Since the correct identification of the problems, quality of other materials used and the on-site workmanship are factors beyond our control, there are no expressed or implied guarantee / warranty as to the results obtained. The company does not assume any liability or consequential damage for unsatisfactory results, arising from the use of our products.

EDITION: 09/2019/001 **IDENTIFICATION NO: PD-347**

Please note that this datasheet supersedes all previous versions.